

**IN THE SPECIFICATION:**

Please amend the specification beginning on page 10, line 3, as follows:

--FIG. 32 is a cross-sectional view of a laminated door skin with molding covering the fold points; ~~and~~

FIG. 33 is a perspective view of a door skin with attached molded; and

FIG. 34 is a perspective view of a door having a door skin according to the present invention prior to installation of molding.--

Please amend the paragraph beginning on page 26, line 5, as follows:

-- One way of addressing the lamination cracks 213 is through the application of an ornamental molding 216. An exemplary cross-section of a door skin 202 with the ornamental molding 216 installed is best shown in Figure 32. The ornamental molding 216 covers the lamination cracks 213, thus precluding them from being seen by consumers. The molding 216 also amplifies the door skin 202 molded recesses and complements the decorative features of the door skin 202. To further enhance the door's appearance, the molding 216 may have a contrasting color to accentuate the contrast between the door skin 202 and the ornamental molding 216. The interior side of the molding 216 conforms to the angular interface surfaces 205, 207, 208, 209 (as best shown in Figure 30) and is fixedly attached to the door skin 202. The molding 216 may

be comprised of solid wood, MDF wrapped with decorative paper or veneer, or the molding may be comprised of any alternate material consistent with the appearance and function of the molding 216. **Figure 34 shows a door manufactured from door skin 202 prior to installation of the molding 216, and** Figure 33 shows a door manufactured from door skin 202 with the molding 216 installed.--